



## Responsibility For Distribution

ZIMCHEM REFINERS (PVT) LTD  
Box 41 Redcliff  
Zimbabwe  
Tel +263 55 62260 /263 55 11 446 002: Fax + 263 55 62262

## 1. Identification of Product and the Company

**Trade Name:** Road Tar 55

**Product Code:** CAS NO 800-47-2

### Identification of the Product

**Type of product:** A blend of tar base oils which is black in colour.  
**Use of product:** Spray type binder for road construction. Tack coat for bottom layer.  
**Company Identification:** See heading on Material Safety Data Sheet  
**Emergency phone number:** See footer on Material Safety Data Sheet

## 2. Composition and Information on Ingredients

A blend of tar based oils used as a spray type binder for road construction. Tack coat for bottom layer.

## 3. Hazard Identification

- \* Toxic (T) : R48/23/24/25-Toxic: danger of serious damage to health by prolonged exposure through inhalation, contact with skin and if swallowed.
- \* Carcinogen (cat.2, T) : R45 -May cause cancer.
- \*Highly flammable (F) : R10-Flammable

## 4. First Aid Measures

**General** : CALL A PHYSICIAN IN ALL CIRCUMSTANCES  
Never give anything by mouth to an unconscious person.

**EMERGENCY NUMBERS: +2635562260, +26323420738**

Remove patient to fresh air away from hazard and remove contaminated clothing. Send for medical attention.  
Remove contaminated clothing and keep patient at rest and warm

**Skin:** -Tar adhering to the skin may be removed by swabbing with vegetable oil  
or using hand cleaner.

-Do not pull adhering material from the skin.

-Hot product should be drenched with cold water to cool.

**Eye:** -Wash eyes with copious amounts of water for at least 15 minutes.

Send for medical treatment thereafter.

**Ingestion:** - DO NOT INDUCE VOMITING. If unconscious wash mouth with plenty of water without  
swallowing. Give 250 ml of water to drink if conscious.

**Inhalation** - Give artificial respiration and give oxygen if necessary.

## 5. Fire Fighting Measures

### Extinguishing Media

-Suitable : Product is flammable.  
Powder, Carbon dioxide, Foam

-Not to be used for safety reasons : Do not use a heavy water stream to fight the fire.

\*Special Procedures : Apply water spray or fog to cool nearby equipment. Avoid fire fighting water to enter  
environment.

\*Special Exposure Hazards : Fire may liberate carbon dioxide and smoke.

Special Protective Equipment for : Use self-contained breathing apparatus when in close proximity to fire.

## 6. Accidental Releases

Personal Precautions : Avoid Every Contact.  
Eliminate every possible source of ignition (open fire, sparks, and smoking)  
Evacuate all personnel immediately and ventilate area. Avoid breathing vapour.  
Avoid contact with skin, eyes, and clothing. Wear recommended protective clothing  
(i.e. breathing apparatus to be worn in confined areas, PVC gloves for hand  
protection, splash proof goggles for eye protection and overalls and work suits to  
cover the body)

Environmental Precautions : Shut off leaks if without risk.  
Cover the spilled product as much as possible with inert material.  
Prevent entry of product in public water, sewers or soil.  
Notify authorities if product enters sewers or public waters

Methods for cleaning up : Collect the spillage in closable, suitable disposal containers.  
Clean up any spills as soon as possible, using an inert absorbent material and

dispose as hazardous waste.

## 7. Handling and Storage

- \* Handling : Avoid every contact  
Avoid breathing vapour and contact with skin and eyes.  
Wear recommended protective clothing.
- \*Protection against Fire and Explosion : Use special care to avoid static electric discharges..  
Vapour is heavier than air and spreads along the ground with risk of ignition at a distance. Always use explosion proof electrical equipment
- \*Storage : Keep only the original container in a cool, well ventilated and fireproof place.
- \*Packing Material : Carbon steel, Stainless steel, Polyester, Teflon

## 8. Measures( Exposure control / Personal Protection)

Engineering Measures to reduce Exposure : Ventilate area  
Industrial Hygiene : When using do not eat, drink or smoke

### Personal Protection Equipment

- \*Respiratory Protection : Ventilation, Local exhaust, Respiratory protection equipment (Filter type A)  
\*Hand protection : Gloves (PVA...)  
Eye protection : Face shield  
: Eye protection combined with respiratory protection equipment.  
Skin and Body Protection : Suitable protective clothing. (Anti-static)

## 9. Physical and chemical properties

E.V.T: - 53°C - 57°C  
Moisture: - 0.5% max  
.Form/colour - Black viscous liquid  
Odour - pungent smell

## 10. STABILITY AND REACTIVITY

Stability : Stable at normal circumstances

## 11. TOXICOLOGICAL INFORMATION

### - Acute toxicity

-Inhalation : High concentrations may produce respiratory problems, lung damage, headaches and dizziness

- Skin contact : Skin cancer can result from tar warts if not treated.
- Eye contact : Irritating to eyes  
Symptoms include: Pain, Redness.
- Ingestion : May cause gastro intestinal complications, sore throat and unconsciousness.

**12.ECOLOGICAL INFORMATION**

- Mobility : Difficult solubility in water.
- Ecotoxicity : Water pollutant

**13.DISPOSAL CONSIDERATIONS**

- Waste from Residues /Unused Products : The product has to be destroyed according to national Or local legislation, or by a company specialised in Handling hazardous waste products.
- Removal of contaminated packaging : Packaging is to be used exclusively for the packaging of this product. After use, empty and close the packaging very carefully.  
In case returned packing the empty packing can be Offered back to the supplier.

**14. TRANSPORT INFORMATION****Land (road /railroad, ADR/RID)**

- ARD Name : Road Tar 55l
- ADR/RID division : 3
- Hazard label(s) : 3
- R-Phrases : R10-Flammable, R45-May cause cancer

**15. REGULATORY INFORMATION**

- Name dangerous component : Road Tar
- Symbol(s) : flammable (F).  
Toxic (T)
- R-Phrases : R10-Flammable  
R45-May cause cancer.  
R48/23/24/25-Toxic: danger of serious damage to health due to prolonged exposure through inhalation ,  
In contact with skin or if swallowed.
- S-Phrases : S45-In case of accident or if you feel unwell, seek Medical advice immediately (show the label if possible)

**16. OTHER INFORMATION**

- This safety data sheet is exclusively made for industrial / professional use
- R-Phrases : R10-Flammable  
: R45-May cause cancer  
: R48/23/24/25-Toxic: danger of serious damage to health by prolonged  
Exposure through inhalation, in contact with skin and if swallowed
- Sources of key data used : the information contained herein is based on the present state of our  
Knowledge (Producer, Chemical cards)

This information to our knowledge is complete on the date of this safety data sheet

The information only concerns the product and does not give any guarantee for the quality and completeness of the properties of the product, or in case of mixing or using in any other process. It means the responsibility of user to ensure himself that ZIMCHEM REFINERS P/L denies all responsibility for loss or damage resulting from the use of this data